

Notified Body No. 2812

Type-Examination (Module B) Certificate

ERO2812/MED0493TERev.1

This is to certify that:

Element Materials Technology Rotterdam B.V. (ERO) did undertake the relevant type approval procedures for the type of equipment identified below which was found to be in compliance with the requirements of Marine Equipment Directive (MED) 2014/90/EU of 23rd July 2014, subject to any conditions in the schedule attached hereto.

Manufacturer

Name

AFS BORU SANAYI A.S

Address

İvedik Organize Sanayi Bölgesi, 1468. Cadde No:153, Ostim 06370,
Ankara, Turkey

Authorised Representative

Name

Authorised Rep Compliance Ltd,

Address

71 Baggot Street Lower, Dublin, D02 P593, Republic of Ireland

Directive reference

Marine Equipment Directive (MED) 2014/90/EU of 23rd July 2014 and
Regulation (EU) 2021/1158/EU of 22nd June 2021

Regulation Item

Item No. MED/3.18f, Combustible Ducts

Product Type

“SLEEVEAFS.B ECOSOFT MARINE”

Product description

Flexible air duct insulation material, as per detail in Attachment to this
certificate

Specified Standard

SOLAS 74, Reg. II-2/3, II-2/5, II-2/9 and X/3, IMO Res MSC.36(63)-(1994
HSC Code) 7, IMO Res MSC.97(73)-(2000 HSC Code) 7, IMO
MSC/Circ.1120, IMO Res. MSC.307(88)-(2010 FTP Code), as amended.

The attached schedule of approval forms part of this certificate.

This certificate remains valid unless suspended, expired or withdrawn, provided the conditions in the attached schedule are complied with.



Pascal Coget
Certification Manager

Date of Issue: 2022-09-05

Expiry date: 2027-09-04

ERO project reference: ERO 034621 P1597

Notes:

- This equipment is covered by the scope of the “Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment” signed February 27th, 2004 and amended by Decision No.1/2008 dated February 18th, 2019 according to U.S Coast Guard approval category 164.112.
- A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F) as allowed by the MED.
- This certificate will not be valid if the manufacturer makes any changes or modifications to the approved type of equipment, which have not been notified to, and agreed with, the notified body named on this certificate.
- During the period of validity of this certificate the applicable regulations (international conventions and the relevant resolutions and circulars of the IMO) and testing standards of the Commission Implementing Regulation may change, therefore the product conformity may need to be re-assessed by the Notified Body.

Appendix to Type-Examination Certificate

Schedule of Approval

The applicant declared that the following comprises an accurate description of the system type to which this certificate applies:

General description		Flexible air duct insulation material
Product reference of overall composite		SLEEVEAFS.B ECOSOFT MARINE
Name of manufacturer of overall composite		AFS BORU SANAYI A.S.
Thickness of overall composite		25mm 33.62 mm (determined by Warringtonfire)
Weight per unit area of overall composite		476 g/m ² (stated by sponsor) 474.6g/m ² (determined by Warringtonfire)
Product configuration		<ul style="list-style-type: none"> • Barrier • Insulation • Jacket <p style="text-align: center;">OR</p> <ul style="list-style-type: none"> • Jacket • Insulation • Barrier
Barrier	Generic type	Compact polyethylene barrier
	Product reference	See Note 2
	Name of manufacturer	See Note 3
	Thickness	0.012 mm
	Density	0.933 kg/m ³
	Colour reference	Transparent
	Flame retardant details	See Note 4
Insulation	Generic type	Glass wool insulation
	Product reference	See Note 2
	Name of manufacturer	KNAUF INSULATION
	Colour reference	Brown
	Thickness	25 mm
	Density	16 kg/m ³
	Flame retardant details	See Note 4
Jacket Poly	Generic type	Polyester
	Product reference	See Note 1
	Name of manufacturer	See Note 1
	Thickness	12 micron
	Density	1.40 g/cm ³
	Colour reference	Transparent
	Flame retardant details	See Note 4

Continued on next page

Jacket (continued)	Poly	Generic type	Polyester
		Product reference	See Note 1
		Name of manufacturer	See Note 1
		Thickness	12 micron
		Density	1.40 g/cm ³
		Colour reference	Transparent
		Flame retardant details	See Note 4
	Aluminium	Generic type	Aluminium foil
		Product reference	See Note 1
		Name of manufacturer	See Note 1
		Colour reference	Aluminium
		Thickness	9 micron
		Density	2.72 g/cm ³
		Flame retardant details	See Note 4
Brief description of manufacturing process			See Note 1

Note 1 - The sponsor was unwilling to provide this information.

Note 2 - The sponsor was unable to provide this information.

Note 3 - The sponsor of the test has provided this information but at the specific request of the sponsor, these details have been omitted from the report and are instead held on the confidential file relating to this investigation.

Note 4 - The sponsor of the test has confirmed that no flame retardant additives were utilised in the production of the product / component.

Type Examination documentation

Test report No.	Date	Product reference	Test method
WF 369725	29th November 2016	SLEEVEAFS.B ECOSOFT MARINE	IMO Resolution MSC.307(88) (2010 FTP Code) : Annex 1 : Part 5
WF 369726	29th November 2016	SLEEVEAFS.B ECOSOFT MARINE	IMO Resolution MSC.307(88) (2010 FTP Code) : Annex 1 : Part 5
Smoke and Toxicity is satisfied by meeting the total heat release (Q _t) and peak heat release (Q _p) requirement as stated Paragraph 2.2 of Annex 2 to IMO Resolution MSC 307(88).		SLEEVEAFS.B ECOSOFT MARINE	IMO Resolution MSC.307(88) (2010 FTP Code) : Annex 1 : Part 2

Production Locations:

Place of production AFS BORU SANAYI A.S, İvedik Organize Sanayi Bölgesi, 1468. Cadde No:153, Ostim 06370, Ankara, Turkey

Restrictions of use

None.

Marking

The Mark of Conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E, or F) of the Directive is fully complied with.

