

## Notified body No. 2812

# Certificate of Type Approval 164.112/ERO2812/MED0493TE

(EC Certificate of Type Examination-2014/90/EU Directive Module B)

Manufacturer: AFS BORU SANAYI A.S Authorised

AFS BORU SANAYI A.S

Representative:

Address: Ivedik Organize Sanayi

Bölgesi 1468. Cadde No:153 OSTIM ANKARA Address: Ivedik Organize Sanayi

Bölgesi 1468. Cadde No:153 OSTIM

ANKARA

This is to certify that the manufacturer has submitted details of a surface material with low flame-spread and low smoke and toxic fume characteristics (Item No. MED/3.18f), known and designated as:-

## "SLEEVEAFS.B ECOSOFT MARINE"

having the technical specification given in the schedule of equipment on this certificate which has been tested and complies with the recommended criteria given in the following methods, published by the International Maritime Organisation, and which are contained in the relevant parts of the International Code for Application of Fire Test Procedures (FTP Code) namely:-

IMO Resolution MSC 307(88): Annex 1: Part 5

IMO Resolution MSC 307(88): Annex 1: Part 2. Smoke and Toxicity is satisfied by meeting the total heat release ( $Q_t$ ) and peak heat release ( $Q_p$ ) requirement as stated Paragraph 2.2 of Annex 2 to IMO Resolution MSC 307(88).

The system complies with the relevant international testing standards under which legislation (The Merchant Shipping Marine Equipment) Regulations 2016 and also the Marine Equipment Directive 2014/90/EU as amended) and the Commission Implementing Regulation 2020/1170/EU of 16<sup>th</sup> July 2020, the certificate is issued.

This equipment is covered by the scope of the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment signed February 27th, 2004 and amended by Decision No.1/2018 dated February 18th, 2019. The manufacturer is allowed to affix the U.S. Coast Guard approval number 164.112/ERO 2812/MED0493.

Janet Murrell

Certification Manager - Marine

Date of issue: 2021-01-01 Valid until: 2021-11-08

ERO project reference: EROMED10007
ERO EC Distinguishing No. 2812

This certificate is not valid for equipment, the design or manufacture of which, has been varied or modified from the specimens tested

CSF402-NL 0.1



## **Certificate of Type Approval Schedule of Equipment**

The applicant declared that the following comprises an accurate description of the system type to which this certificate applies:

General descripti		Flexible air duct insulation material		
	e of overall composite	SLEEVEAFS.B ECOSOFT MARINE		
Name of manufac	cturer of overall composite	AFS BORU SANAYI A.S.		
Thickness of overall composite		25 – 50 mm 33.62 mm (determined by <b>Warringtonfire</b> )		
Weight per unit a	rea of overall composite	476 g/m² (stated by sponsor) 474.6g/m² (determined by <b>Warringtonfire</b> )		
Product configuration		<ul><li>Barrier</li><li>Insulation</li><li>Jacket</li></ul>		
	Generic type	Compact polyethylene barrier		
	Product reference	See Note 2		
	Name of manufacturer	See Note 3		
Barrier	Thickness	0.012 mm		
	Density	0.933 kg/m <sup>3</sup>		
	Colour reference	Transparent		
	Flame retardant details	See Note 4		
	Generic type	Glass wool insulation		
	Product reference	See Note 2		
	Name of manufacturer	KNAUF INSULATION		
Insulation	Colour reference	Brown		
	Thickness	25 mm		
	Density	16 kg/m <sup>3</sup>		
	Flame retardant details	See Note 4		



JACKET	Poly	Generic type	Polyester	
		Product reference		See Note 1
		Name of manufacturer		See Note 1
		Thickness	12 micron	
		Density	1.40 g/cm <sup>3</sup>	
		Colour reference	transparent	
		Flame retardant details		See Note 4
	Poly	Generic type	Polyester	
		Product reference		See Note 1
		Name of manufacturer	W	See Note 1
		Thickness	12 micron	9: S
		Density	1.40 g/cm <sup>3</sup>	
		Colour reference	transparent	
		Flame retardant details	5	See Note 4
	Aluminium	Generic type	Aluminium foil	
		Product reference		See Note 1
		Name of manufacturer	///	See Note 1
		Colour reference	Aluminium	
		Thickness	9 micron	
		Density / weight per unit area	2.72 g/cm <sup>3</sup>	
		Flame retardant details	- Fa	See Note 4
Brief description of manufacturing process				See Note 1

- **Note 1** The sponsor was unwilling to provide this information.
- **Note 2** The sponsor was unable to provide this information.
- **Note 3** The sponsor of the test has provided this information but at the specific request of the sponsor, these details have been omitted from the report and are instead held on the confidential file relating to this investigation.

**Note 4** - The sponsor of the test has confirmed that no flame retardant additives were utilised in the production of the product / component.

The under noted documents have been approved for compliance with the relevant requirements of International Conventions and European Union Legislation for the EC Type examination of Marine Equipment for use on Ships Registered in the European Economic Area.

## **Approved Documents**

## **Test Reports**

- (1) WARRES No. 369725 (dated August 2016). Surface Flammability test to IMO Resolution MSC 307(88) Annex 1 Part 5 and annex 2 of the Fire Test Procedures Code.
- (2) WARRES No. 369726 (dated August 2016). Surface Flammability test to IMO Resolution MSC 307(88) Annex 1 Part 5 and annex 2 of the Fire Test Procedures Code.
- (3) Smoke and Toxicity is satisfied by meeting the total heat release (Q<sub>t</sub>) and peak heat release (Q<sub>p</sub>) as stated in IMO Fire Test Procedures Code, Annex 2 Section 2.2

164.112/ERO2812/MED0493TE